

EAM DELTA WIPE-ON LABEL APPLICATOR

EAM Delta Features

- Intuitive set-up (speeds, tag location, skipping) through OIT touch screen.
- Can be used to apply a wide range of adhesive labels, including long format labels (send us your product for testing)
- Applies Many styles of labels including EAS tags, Hang Tags, Coupon Booklets, Graphic Labels, Etc.
- Please feel free to send samples of your product for compatibility testing.
- Custom dispense options available to meet your application needs.
- The Delta Wipe-On can accommodate many web widths with the installation of custom multi width heads.
- The Delta can read a line-speed encoder and is capable of speed compensation for improved tag placement accuracy.
- Micro-Stepper web drive system for high-speed repeatability.
- Includes Mechanical Unwind, optional powered unit available for high-speed applications.



EAM Delta Technical Data

Standard Service Requirements:

- 120 VAC, Single \emptyset , < 3 Amp
- 85 PSI (5.8 bar), < 2CFM (56 ℓ pm)

High Voltage Service Requirements:

- Several voltages available.
To be determined based on customer requirements.

Machine Dimensions:

- 12" (h) x 11.25" (w) x 27.25" (l)
(305mm x 285mm x 692mm)

Remote Enclosure Dimensions:

- 10"(h) x 12"(w) x 6" (d)
(254mm x 305mm x 152mm)

Weight (without options):

- Approximately 25 lbs. (11.3 kg)
Depending on included options.

Maximum Rate Speed:

- Rates up to 550 tags per minute

Web Width:

- Standard unit up to 4" Web width.
Other custom configurations available.

Note: Seemingly small variations in product can often affect run-ability. Even if your product appears to be well within the Delta specifications, EAM strongly encourages you to submit samples for evaluation.