

## EAM DELTA TAG APPLICATOR

### *EAM Delta Features*

- Intuitive set-up (speeds, tag location, skipping) through OIT touch screen.
- Can be used to apply a wide range of adhesive labels
- Applies RF – Checkpoint – All-Tag Anti-theft tags
- Applies Sensormatic Ultra-Strip Anti-theft tags
- The Delta can accommodate web widths up to 3.5" (88mm).  
*Note: Wide format Delta is also available.*
- The Delta can read a line-speed encoder and is capable of speed compensation for improved tag placement accuracy.
- Micro-Stepper web drive system for high speed repeatability.



### *EAM Delta Technical Data*

#### **Standard Service Requirements:**

- 120 VAC, Single  $\emptyset$ , < 3 Amp
- 85 PSI (5.8 bar), < 2CFM (56  $\ell$ pm)

#### **High Voltage Service Requirements:**

- Several voltages available.  
*To be determined based on customer requirements.*

#### **Machine Dimensions:**

- 17.8"(h) x 7.6"(w) x 9.9" (d)  
(450mm x 193mm x 250mm)

#### **Remote Enclosure Dimensions:**

- 10"(h) x 12"(w) x 6" (d)  
(254mm x 305mm x 152mm)

#### **Weight (without options):**

- Approximately 25 lbs. (11.3 kg)  
*Depending on included options.*

#### **Maximum Rate Speed:**

- Rates up to 550 tags per minute  
*Depending on stroke and tag type*

#### **Tamp Head Stroke Range:**

- 15mm (min) to 40mm (max)  
*Longer strokes available on request.*

#### **Web Width:**

- 1.5" (38mm) Min. to 3.5" (89mm) Max.  
*Wider web available on request.*

### *EAM Delta Available Options*

- Floor Stand-Vertically adjustable, heavy duty and low-toe versions available
- Horizontal Adjust
- Powered Reel Unwind
- Tamp heads for various strokes and types of labels
- Multi-head Controller allows up to six Deltas to run together

**Note:** Seemingly small variations in product can often affect run-ability. Even if your product appears to be well within the Delta specifications, EAM strongly encourages you to submit samples for evaluation