

EAM MINI ST-300 SOURCETAG APPLICATOR

EAM MiniST-300 Features

- Applies Sensormatic Ultra-Strip III Anti-theft tags (DR Tags)
- AC-Stepper web drive system for high speed repeatability.
- Can be mounted in virtually any orientation and in very tight spaces.
- PLC controls included-no umbilical cord or external control enclosure.



EAM ST-300 Technical Data

Standard Service Requirements:

- 120 VAC, Single \emptyset , < 3 Amp
- 85 PSI (5.8 bar), < 2CFM (56 ℓ pm)

High Voltage Service Requirements:

- Several voltages available.
To be determined based on customer requirements.

Machine Dimensions:

- 12.8"(h) x 8.5"(w) x 6.5" (d)
(325mm x 216mm x 165mm)

Weight (without options):

- Approximately 14-25 lbs. (6.4-11.3 kg)
Depending on included options.

Maximum Rate Speed:

- Rates up to 250 tags per minute
Depending on stroke

Tamp Head Stroke Range:

- 20mm (min) to 45mm (max)

Web Width:

- 2.1" (53mm)
Runs Sensormatic Tags Only.

EAM MiniST-300 Available Options

- Floor Stand-Vertically adjustable, heavy duty and low-toe versions available
- Pivot Mounting Base (w/swivel option)
- Horizontal Adjust
- Powered Reel Unwind
- Various strokes available

Note: Seemingly small variations in product can often affect run-ability. Even if your product appears to be well within the FG-24 specifications, EAM strongly encourages you to submit samples for evaluation

